

AIVIS-C60



Close-up Lens	Image Sensor	1/2.8-inch CMOS, 2.14M
	Focal Length	f=4.14mm-47.08mm
	Aperture	F1.6-F2.8
	Optical Zoom	12X
	Digital Zoom	16X
	Focus System	Automatic, Manual, PTZ Trigger, One-touch Trigger
	Min Illumination	0.5Lux
	Shutter Speed	1/60-1/10,000s
	Gain	Automatic, Manual
	Exposure Control	Automatic, Manual, Shutter Priority, Aperture Priority, Brightness Priority
Panoramic Lens	Image Sensor	1/2.8-inch CMOS, 2.14 Megapixels
	Focal Length	f=1.89mm
	Horizontal Field of View	110°
	Horizontal Field of View	Automatic
	Exposure Control	Automatic
Smart MIC Array	Mic Array	8-array Mic
	DOA Accuracy	<5°
	Max Detection Distance	8m
PTZ Function	Horizontal Rotation Range	-130°~+130°
	Vertical Rotation Range	-30°~+90°
	Horizontal Rotation Speed	0.1°~100°/s
	Vertical Rotation Speed	0.1°~80°/s
	Number of Preset Points	64
Interface	Network	1 Port, 10/100M RJ-45 POE
	3G-SDI	1 Port, 3G-SDI
	HDMI	1 Port, HDMI Out
	USB 2.0	1 Port, USB 2.0 Type-A HOST
	USB 3.0	1 Port, USB 3.0 Type-B
	Audio Interface	1 Port, LINE IN, 3.5mm
	Reference Audio	1 Port, REF, 3.5mm
	Control Interface	1 Port, RS-485 1Port, RS-232 IN
	Power Interface	DC12V
	Power Switch	Boat-shaped Switch
	Wireless Control	Infrared Remote Control
Infrared Remote Control	Infrared Remote Control	VISCA
	Power Consumption	<20W
	Operating Environment	Operating Temperature, 0~40°C; Operating Humidity, 10%RH ~90 %RH
	Storage Environment	Storage Temperature, -20°C~60°C; Storage Humidity, 10%RH~90 %RH
	Dimensions	245mm*145mm*165mm
	Weight	<2KG
Certification	Firmware Upgrade	Support
	Status Query	Support

